

Enclosures

<b>Material</b>	DMC (Dough Moulding Compound)
<b>Operating Temperature</b>	-50° C to + 200° C
<b>Glow Wire Capability / Flammability</b>	960° / UL94 V0
<b>Expected UV Life (Direct Exposure)</b>	GRP Flap 25 years + , Plastic Flap
<b>IP Level</b>	IP4X
<b>Security Level</b>	Level 1 without pad-lock and Level 3 with pad-lock

Hinges

Locks

Handles

Accessories

Rotary Operating  
Handles


Insulators

Transformer  
Equipment

Index



Part Number	Description	H (mm)	W (mm)	D (mm)
040-964	4 Way Surface ADB GRP Flap	187	165	110
040-965	8 Way Surface Din ADB GRP Flap	216	266	111
040-981	8 Way Flush Din ADB GRP Flap	216	266	111
040-980	8 Way Surface Din ADB Plastic Flap	216	266	111
040-968	8 Way Flush Din ADB Plastic Flap	216	266	111
040-982	8 Way Surface Samite ADB GRP Flap	216	266	111
040-983	8 Way Flush Samite ADB GRP Flap	216	266	111
040-984	8 Way Surface Samite ADB Plastic Flap	216	266	111
040-985	8 Way Flush Samite ADB Plastic Flap	216	266	111



**Pad-lockable**  
ADB- Distribution Boards fits pad-lock size 262,  
\*Size may vary according to make.

