

Enclosures

Hinges

Locks

Handles

Accessories

Rotary Operating
Handles

Insulators

Transformer
Equipment

Index

Air- to-air Type



Part Number	Description	U.m (kV)	Ir (A)	Tank Hole Size (mm)	ACSD - 60 Sec (kV)	Stem Diameter	Stem Thread Size	Stem Pitch (mm)	Recommended Stem Torque (N.m)
070-392	FB10 Flame Proof	1.1	80	21	7.5	M10	M10	1,5	8
040-015	AA-062/250	7.2	250	50	18	M12	M12	1,75	16
040-019	AA-062-630	7.2	630	50	18	M20	M20	2	22
040-016	AA-112/250	12	250	50	30	M12	M12	1,75	16
040-017	AA-112/630	12	630	50	30	M20	M20	2	22
040-014	AA-113/250	12	250	50	30	M12	M12	1,75	16
040-020	AA-113/630	12	630	50	30	M20	M20	2	22

*** Note:**

Detailed drawings available on request

Tank wall thickness minimum 3mm , maximum 6mm

Tank hole size tolerance is -0mm +1mm

Cable Box Type



Part Number	Description	U.m (kV)	Ir (A)	Tank Hole Size (mm)	LI	Stem Diameter	Stem Thread Size	Stem Pitch (mm)	Recommended Stem Torque (N.m)	ACSD (kV)
040-208	SM250	12 *	250	50	N/A	M12	M12	1,75	16	30
040-005	IM250	12	250	50	N/A	M12	M12	1,75	16	30
040-032	CF1	22	630	72	N/A	OD=20 , Tapped M12	M16	2	16	50

*** 7.2Kv Outdoor Rating**

*** Note:**

Detailed drawings available on request

Tank wall thickness minimum 3mm , maximum 6mm

Tank hole size tolerance is -0mm +1mm